

CITY OF CHARLOTTE

NEIGHBORHOOD & BUSINESS SERVICES

Invitation to Bid NBS-20-52

NOTE: Contractors are not authorized to visit the property before or after the bid walk, without being accompanied by the City's Rehabilitation Specialist.

Documents included in Package:

- 1) Instruction to Bidders
- 2) Specs by Location/Trade (Scope of Work)
- 3) Subcontractor Certifications (if applicable)
- 4) Floor Plan / Site Drawing (if applicable)

Bid Walk & Bid Opening:	NB	S-20	-52

Project Address:	4608 HIDDEN VALLEY ROAD	SAFE HOME
Bid Walk:	THURSDAY FEBRUARY 13, 20	20 @ 1:00 PM
Bid Opening:	THURSDAY FEBRUARY 20, 20	29 @ 2:00PM
Client Name:	,	Contact Number:
Project Manager:	James Mahon	Contact Number: 704-432-2321

Bid Walk and Bidding Instructions:

All bid walks are mandatory.

If you are going to be late the policy is the following:

Contact me BEFORE the start time if you are going to be late. If you are going to be more than 10 minutes late, we will proceed without you and you will not be permitted to bid.

The day of a bid walk the best way to reach me is at <u>James Mahon</u> (cell # 704-614-6655).

Bids must be received by the date, time and place specified. All others will be considered non responsive and disqualified.

The Bids will be opened at 600 East Trade St. immediately following the

G:\SELECTIVE REHAB TEAM\forms\bid forms and documents\Invitation to bid WARREN

DN



CITY OF CHARLOTTE

NEIGHBORHOOD & BUSINESS SERVICES

above due date and time.

Please Print and Sign:

Company Name/Firm:

Signature:

Authorized Representative Name:

Company Acknowledgement:		·
provisions of the housing improvement be funded through the City of Charle having fully inspected the site in all part within the time stated and in strict accordance with the advised respective.	nent work to be per otte Neighborhood ticulars, hereby prop cordance with the pro erials, and to do all w e contractual, for the quipment necessar	poses and agrees to fully perform the work oposed contract documents including work required to complete said Work in
		Dollars (\$
Written total		
Specs Dated: 02/04/2020	Number of Pages:	9 REHAB
Addenda # 1 Dated:	Number of Pages:	
Addenda # 2 Dated:	Number of Pages:	
Project Schedule: Minimum Start Dat	e -	
Completion Deadline:		

Date:



SAFE HOME CITY OF CHARLOTTE

NEIGHBORHOOD & BUSINESS SERVICES

Requirements For Bidders

The City awards rehabilitation bids to the lowest responsive and responsible bidder. A responsible bidder for the safe home program is one who:

- 1) Is a licensed general contractor in the State of North Carolina;
- 2) Has an Renovate, Repair & Paint Certification (http://www2.epa.gov/lead/renovation-repair-and-painting-program);
- 3) Is not listed on a local, state or federal debarment list;
- 4) Carries an appropriate amounts of insurance;
- 5) Can provide references verifying the contractor has completed work of a similar scope in a good workmanship like manner or successfully completed prior work for the Safe Home program. Referenced work must have been completed in one year or less from date of this invitation to bid.

A responsive bidder must:

- 1) Submit all requested documentation on time;
- 2) Meet the above requirements for responsibility at the time of bid submittal;
- 3) Have the capacity to meet the required schedule for the project.
- 4) Existing rehab projects contracted by the contractor must be on schedule.

The City reserves the right to waive any minor informalities or irregularities, which do not go to the heart of the bid submittal or prejudice other offers, or to reject, for good and compelling reasons, any or all bid submittals.

James Mahon Rehabilitation Specialist City of Charlotte Neighborhood and Business Services 600 E. Trade St. Charlotte, NC 29202

PH: (704) 432-2321 Fax: (704) 336-3489



CITY OF CHARLOTTE

NEIGHBORHOOD & BUSINESS SERVICES

Instructions to Bidders

Explanations to Bidders

Any explanation desired by a Contractor regarding the meaning or interpretation of the advertisement for bids, drawings, specifications, etc., must be requested in writing to the Rehabilitation Specialist with sufficient time allowed for a reply to each Contractor before the submission of their bids. Any interpretation made will be in the form of an addendum to the invitation for bids, drawings, specifications, etc., and will be furnished to all prospective Contractors. The Contractor must acknowledge any revision to the bid documents in the space provided on the bid form and it must be submitted with their bid package.

Preparation of Bids

Bids shall be submitted on the forms furnished, or copies thereof, and must be manually signed. If erasures or other changes appear on the forms, the person signing the bids must initial each erasure or change

- The Contractor's Bid Proposal must be properly executed and submitted on the form provided. Bids by Contractors must be received by the Rehabilitation Specialist at the time and place specified on the "Invitation to Bid"
- No bid will be considered unless all individual work items on the Bid Form including any addendums are priced. The sum of all work items must equal to the Total Bid Amount.
- Unless called for, alternate bids will not be considered
- Modification of bids already submitted will be considered if received at the office designated in the invitation for bids by the time set for opening of bids

Submittal of Bids

- Sealed bids will be submitted to the Safe Home Program Office as directed in the invitation to bid prior to or at the appointed bid opening time
- Bid will be time stamped on the date of delivery
- Each bid must be submitted in a sealed envelope bearing on the outside the name of the Contractor, the name of the project for which the bid is submitted, and the date and time of the bid opening
- All bids submitted must be typed or written in ink and signed by the Contractor's designated representative



CITY OF CHARLOTTE

NEIGHBORHOOD & BUSINESS SERVICES

- Failure to include all forms may result in rejection of a bid
- Required Bid Package Forms:
 - Scope of Work
 - o Addenda Acknowledgement
 - o Itemized Work Sheet
 - o Subcontractor Certifications (if applicable)

NEIGHBORHOOD & BUSINESS SERVICES

http://housing.charlottenc.gov | 600 E. Trade Street | Charlotte, NC

Prepared By:

City of Charlotte Housing & Neighborhood Services 600 E. Trade Street Charlotte, NC 28202 (704) 336-7600

P	ro	ne	rfv	'n	eta	ils
	ı	nc	1	ע	GLG	шJ

Address:

4608 Hidden Valley Rd

Charlotte, NC 28213

Structure Type:

Single Unit

Square Feet:

1150

Year Built:

1961

Property Value:

79200

Tax Parcel:

08904751

Census Tract:

Property Zone:

Council District 4

Additional Comments

Bid walk on 2-13-2020 at 1PM.

Repairs

Description

Floor

Room

John Crawford

Tested- NO LEAD

SH2019 Eligible

SHFY19 Pre-Approved

Cell: (704) 208-8104 xgrandson

Owner:

Owner Phone:

Program(s):

Response Due: 2/20/2020 2:00 PM

Exterior

Ceiling Fan with Light Kit-KITCHEN

KITCHEN

Install a 52" 3 speed flush mounted ceiling fan with a minimum two bulb UL approved, LED light fixture with shade and lamps. Include ceiling fan mounting box. New fan is to be Energy Star rated.

			Dase	
 	 *** * ****			-

Quantity

Total Cost

Floor System Repair -KITCHEN

KITCHEN

Remove all fixtures not built in. Dispose of damaged/unsafe components of floor assembly. Work may include installation of 2"x 8" joists hung 16" on center, plywood or tongue and groove subfloor. Include replacing all deteriorated band joists and insulating floor to code.



Bid Cost:	>	(=
	Baco	Quantitu	Total Cost

ase Quantii

Total Cost

Counter Tops Replace

Screw to base cabinet a square edged plastic laminate counter top. Provide end-caps and cutout for sink. Caulk counter top to adjoining walls with low VOC caulking to match wall color. Owner's choice of in-stock color and texture.

KITCHEN

	Bid Cost:		(=	
		Base	Quantity	Total Cost
ouble Bowl Sink Complete	A CAMP OF THE STATE OF THE STAT	5.00 EF 1.2 1 1.1	KITCHEN	and the second of the second o
istall a 18 gauge 33" x 22" x 8" double bowl, stainless ated at 2.0 GPM or less, with a 15 year drip- free war n all supply & drain lines. No copper compression fitti	ranty, P-trap, supply line	en sink inclue s, full port ba	ding a single hand Ill type shut-off val	le metal body faucet, ves & escutcheon plat
	Bid Cost:		X:	3
		Base	Quantity	Total Cost
FCI Receptacle 20 AMP-kITCHEN			KITCHEN	
nstall a flush mounted, ground fault circuit interrupted	, duplex receptacle and o	cover plate. F	ish wire and repai	r all tear out as needed
•	Bid Cost:		X	=
	Bid Cost	Base	Quantity	Total Cost
				A CONTRACTOR OF STREET
Resilient Flooring-kITCHEN nstall 25 year warrantied resilient floor covering per m quarter-round at all perimeters to complete installation		ons. Include t	KITCHEN ransitions and pai	nted or stained wood
nstall 25 year warrantied resilient floor covering per m				nted or stained wood Total Cost
nstall 25 year warrantied resilient floor covering per m juarter-round at all perimeters to complete installation			ransitions and pai	
nstall 25 year warrantied resilient floor covering per m	Bid Cost:	Base	X Quantity KITCHEN	=Total Cost
nstall 25 year warrantied resilient floor covering per mularter-round at all perimeters to complete installation -aundry Washer Connection Box nstall PVC vent pipe through the roof, laundry connection	Bid Cost:	Base Id hose bibbs	X Quantity KITCHEN s, and 20 amp outl	=Total Cost
nstall 25 year warrantied resilient floor covering per muarter-round at all perimeters to complete installation	Bid Cost:	Base Id hose bibbs	X Quantity KITCHEN	=Total Cost
nstall 25 year warrantied resilient floor covering per muarter-round at all perimeters to complete installation -aundry Washer Connection Box nstall PVC vent pipe through the roof, laundry connectors service a washing machine.	Bid Cost:	Base Id hose bibbs	Quantity KITCHEN s, and 20 amp outl	Total Cost et on a separate circuit Total Cost
nstall 25 year warrantied resilient floor covering per muarter-round at all perimeters to complete installation -aundry Washer Connection Box nstall PVC vent pipe through the roof, laundry connector service a washing machine.	Bid Cost: Stion box with hot and co Bid Cost: Smoke and heat detector	Base Id hose bibbs	Quantity KITCHEN s, and 20 amp outl X Quantity	Total Cost et on a separate circuit Total Cost
nstall 25 year warrantied resilient floor covering per marter-round at all perimeters to complete installation aundry Washer Connection Box enstall PVC vent pipe through the roof, laundry connect o service a washing machine. Smoke Detector Hard Wired enstall UL approved, interconnected, ceiling mounted	Bid Cost: Stion box with hot and co Bid Cost: Smoke and heat detector	Base Id hose bibbs Base	Quantity KITCHEN s, and 20 amp outl X Quantity	Total Cost et on a separate circuit Total Cost

Combination CO / Smoke Detector Hard Wired

GEN REQ

Install a hard wired combination carbon monoxide and smoke detector with battery back up.

	Bid Cost:	X		
		Base	Quantity	Total Cost
Electric Service 200 AMP	e e e e e e e e e e e e e e e e e e e	*	GEN REQ	
Replace electrical service with new 200 amp, main disconnect service cable, ground rods and cable. Include replacement of	, 110/220 volt, 2 all sub-panels.	24 circuit panel be Caulk exterior se	oard, meter socket, vrvice penetration.	weather head,
	Bid Cost:	X	=	
		Base	Quantity	Total Cost
Replace Receptacles, Switches, and Plates			GEN REQ	e i santa e la companya de la compa
Replace all receptacles, switches and cover plates throughout wall or ceiling damage repairs.	t entire house.	Use code approp	riate devices. This a	also includes any
	Bid Cost:	X	=	
		Base	Quantity	Total Cost
Ceiling Fan with Light Kit- LR	w was and	The second way of a name of	LIVING ROOM	Exterior
Install a 52" 3 speed flush mounted ceiling fan with a minimun ceiling fan mounting box. New fan is to be Energy Star rated.		pproved, LED lig	nt fixture with shade	and lamps. Include
	Bid Cost: _	Х	=	
		Base	Quantity	Total Cost
Prehung Door Interior	en e	and the second of the second	LIVING ROOM	Exterior
Install a 1- 3/8" prehung, door including casing both sides and	l lockset. Match	existing style an	d finish.	
	Bid Cost: _	X_		Land Control of the C
		Base	Quantity	Total Cost
	****	****		

Prehung Metal Door Entrance

EXTERIOR

Exterior

Remove existing door, frame and threshold. Install new Energy Star rated pre-hung exterior door. Insulate cavity. Install mortised dead bolt and lever handled door hardware keyed alike. Install wide peep sight. New casing and shoe molding will match existing. Apply primer and topcoat. This installation to include repairing any damaged header, door framing, to include wall framing, sub-floor, floor joists and sill.

Front & Rear.				
	Bid Cost:	х	10A4	
		Base	Quantity	Total Cost
Aluminum Storm Door	garanta da seria da seria da seria de la composición del composición de la composici	to Maria and Company to	EXTERIOR	Exterio
nstall an aluminum combination storm and screen doo Front & Rear	r. Complete with self clo	ser and locking	hardware.	
	Bid Cost:	x_	=	
		Base	Quantity	Total Cost
 A series of the s			BATHROOM	- MAIN
Remove all fixtures not built in. Dispose of damaged/u oists hung 16" on center, plywood or tongue and groo	nsafe components of flove ve subfloor. Include repla	or assembly. Wacing all deterio	Vork may include i	nstallation of 2"x 8" and insulating floor to
Remove all fixtures not built in. Dispose of damaged/u oists hung 16" on center, plywood or tongue and groo	e subfloor. Include repl	acing all deterio	Vork may include i rated band joists ส	nstallation of 2"x 8" and insulating floor to
Remove all fixtures not built in. Dispose of damaged/u loists hung 16" on center, plywood or tongue and groo	nsafe components of flove subfloor. Include replace to the subfloor include replace to the subfloor. Bid Cost:	or assembly. Wacing all deterio	Vork may include i rated band joists ส	nstallation of 2"x 8" and insulating floor to
Remove all fixtures not built in. Dispose of damaged/u oists hung 16" on center, plywood or tongue and groov code.	e subfloor. Include repl	acing all deterio	Vork may include i rated band joists a	Total Cost
Remove all fixtures not built in. Dispose of damaged/u oists hung 16" on center, plywood or tongue and groot code. Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of single handled metal faucet with drain and pop-up, P-	ve subfloor. Include replace Bid Cost:	acing all deterio X Base hina sink or mai	Vork may include is rated band joists a second seco	Total Cost - MAIN reformed sink, Include
Remove all fixtures not built in. Dispose of damaged/u oists hung 16" on center, plywood or tongue and groov code. Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of single handled metal faucet with drain and pop-up, P-	ve subfloor. Include replace Bid Cost:	acing all deterio X Base hina sink or mai	Vork may include is rated band joists a second seco	Total Cost - MAIN reformed sink, Include
Remove all fixtures not built in. Dispose of damaged/u oists hung 16" on center, plywood or tongue and groov code. Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of single handled metal faucet with drain and pop-up, P-	e subfloor. Include replace Bid Cost: laminate with vitreous countrap, supply lines, full po	X Base hina sink or maiort ball type shu	Vork may include is rated band joists a second seco	Total Cost - MAIN reformed sink, Include
Remove all fixtures not built in. Dispose of damaged/u oists hung 16" on center, plywood or tongue and groot code. Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of single handled metal faucet with drain and pop-up, P-Vanity medicine cabinet/mirror to remain.	e subfloor. Include replace Bid Cost: laminate with vitreous countrap, supply lines, full po	X Base hina sink or maiort ball type shu	Vork may include it rated band joists a graded band joists a grade	Total Cost - MAIN reformed sink, Includitcheon plates. Total Cost
Remove all fixtures not built in. Dispose of damaged/u oists hung 16" on center, plywood or tongue and groot code. Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of single handled metal faucet with drain and pop-up, P-Vanity medicine cabinet/mirror to remain. Resilient Flooring-MAIN BATH Install 25 year warrantied resilient floor covering per m	Bid Cost: laminate with vitreous c trap, supply lines, full po	X Base hina sink or manort ball type shut X Base	Quantity BATHROOM Control of the con	Total Cost - MAIN reformed sink, Includitcheon plates. Total Cost
Floor System Repair -MAIN BATH Remove all fixtures not built in. Dispose of damaged/u joists hung 16" on center, plywood or tongue and groot code. Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of single handled metal faucet with drain and pop-up, P-Vanity medicine cabinet/mirror to remain. Resilient Flooring-MAIN BATH Install 25 year warrantied resilient floor covering per m quarter-round at all perimeters to complete installation	Bid Cost: laminate with vitreous cotrap, supply lines, full potentials. Bid Cost: anufacturer's specification.	X Base hina sink or manort ball type shut X Base	Vork may include it rated band joists a graded band joists a graded band joists a graded band joists a graded band it was a graded band and paint of the same and paint of the s	Total Cost - MAIN reformed sink, Includitcheon plates. Total Cost

Bath Exhaust Fan Replace-MAIN

BATHROOM - MAIN

Install a ceiling or through-the-wall, exterior ducted, vent fan with damper. Include power and switch wiring using #14 copper Romex. Repair any tear out.

	Bid Cost:	· · · · · · · · · · · · · · · · · · ·	_x	=	
		Base	Qu	antity	Total Cost
Prep & Paint Room Semi Gloss- MAIN	e ee a wasse s	in it makes the	В	ATHROOM	- MAIN
Remove or cover hardware and accessories not to be painte fungus, dirt, and dust from surfaces. Fill holes and cracks. P with owner's choice of low VOC acrylic SEMI-GLOSS latex. hardware, fixtures and accessories. Any moving of furniture * Ceiling, walls and trim.	rime all new mate Painting shall inc	rials and spo lude walls ar	ot prime ex	disting with a	crylic latex. Top coat
	Bid Cost:		_x	=	
		Base	Qι	antity	Total Cost
17" Height Commode Replace - MAIN		. ,	В	ATHROOM	- MAIN
Install a 17" height, 2 piece, close coupled, white, vitreous of Include plastic or pressed wood white seat, supply pipe, shu				sage per flus	sh of 1.6 gallons.
	Bid Cost:		_X	=	
		Base	Qu	ıantity	Total Cost
GFCI Receptacle 20 AMP - MAIN	a communicación de la estación		E	ATHROOM	- MAIN
Install a flush mounted, ground fault circuit interrupted, dupl	lex receptacle and	cover plate.	. Fish wire	and repair a	ll tear out as needed
	Bid Cost:		Х	=	
		Base		uantity	Total Cost
Light Fixture Replace-MAIN BATH			E	BATHROOM	- MAIN
Replace or install a ceiling mounted 2 bulb or wall mounted	4 bulb strip, UL a	pproved, LE	ED light fixt	ure with sha	de and lamps.
•	DU 0 (v		
	Bid Cost: _	Base	_X Qı		Total Cost
CONTRACTOR OF THE CONTRACTOR O		1		BEDROOM 2	
Ceiling Fan with Light Kit - BR#2 Install a 52" 3 speed flush mounted ceiling fan with a minim	num two bulb UL a	pproved, LE			
ceiling fan mounting box. New fan is to be Energy Star rate			Ü		·
	Bid Cost: _		Х	=	

Ceiling Fan with Light Kit-BRM

BEDROOM - MASTER

Install a 52" 3 speed flush mounted ceiling fan with a minimum two bulb UL approved, LED light fixture with shade and lamps. Include ceiling fan mounting box. New fan is to be Energy Star rated.

	Bid Cost:		Х			
·		Base	-	Quantity		Total Cost
Floor System Repair - HALF BATH	grand and an anti-	ova programa i de estado a	****	BATHRO	OM - H	ALF
Remove all fixtures not built in. Dispose of damaged/unsa oists hung 16" on center, plywood or tongue and groove s code.	afe components of fl subfloor. Include rep	oor assembly acing all del	y. Wo teriora	rk may includ ted band jois	de inst its and	allation of 2"x 8" insulating floor t
	Bid Cost:		_x		=	A APPLICATION OF THE PROPERTY
		Base		Quantity		Total Cost
Resilient Flooring - HALF BATH			•	BATHRO	OM - F	IALF
install 25 year warrantied resilient floor covering per mant quarter-round at all perimeters to complete installation.	ufacturer's specificat	ions. Include	trans	itions and pa	inted o	or stained wood
			v		_	
	Bid Cost:		_^_			
·	Bid Cost:	Base	_*	Quantity		Total Cost
17" Height Commode Replace	Bid Cost:		X			
17" Height Commode Replace Install a 17" height, 2 piece, close coupled, white, vitreous	s china commode wi	Base th a maximu	m wat	Quantity BATHRO	ом - Н	IALF
17" Height Commode Replace Install a 17" height, 2 piece, close coupled, white, vitreous	s china commode wi	Base th a maximulative and wax	m wat	Quantity BATHRO	OM - H	HALF of 1.6 gallons.
17" Height Commode Replace Install a 17" height, 2 piece, close coupled, white, vitreous Include plastic or pressed wood white seat, supply pipe, s	s china commode wi shut-off valve, flap va Bid Cost:	Base th a maximulative and wax	m wat	Quantity BATHRO er usage per Quantity	OM - H	HALF of 1.6 gallons. Total Cost
17" Height Commode Replace Install a 17" height, 2 piece, close coupled, white, vitreous Include plastic or pressed wood white seat, supply pipe, s Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of lar single handled metal faucet with drain and pop-up, P- tra	s china commode wi shut-off valve, flap va Bid Cost: minate with vitreous	Base th a maximu alve and wax Base	m wat c seal. X	Quantity BATHRO er usage per Quantity BATHRO le-lite top wit	OM - I	HALF of 1.6 gallons. Total Cost HALF ormed sink. Inclu
17" Height Commode Replace Install a 17" height, 2 piece, close coupled, white, vitreous Include plastic or pressed wood white seat, supply pipe, s Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of lar single handled metal faucet with drain and pop-up, P- tra	s china commode wi shut-off valve, flap va Bid Cost: minate with vitreous ap, supply lines, full p	Base th a maximu alve and wax Base	m wat c seal. X	Quantity BATHRO er usage per Quantity BATHRO le-lite top wit	OM - I	HALF of 1.6 gallons. Total Cost HALF ormed sink. Inclu
17" Height Commode Replace Install a 17" height, 2 piece, close coupled, white, vitreous Include plastic or pressed wood white seat, supply pipe, s Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of lar single handled metal faucet with drain and pop-up, P- tra	s china commode wi shut-off valve, flap va Bid Cost: minate with vitreous	Base th a maximu alve and wax Base	m wat c seal. X	Quantity BATHRO er usage per Quantity BATHRO le-lite top wit	OM - I	HALF of 1.6 gallons. Total Cost HALF ormed sink. Inclu
17" Height Commode Replace Install a 17" height, 2 piece, close coupled, white, vitreous include plastic or pressed wood white seat, supply pipe, so a variety of the variety of the variety Counter Top/ Sink Install new vanity cabinet complete with counter top of lar single handled metal faucet with drain and pop-up, P- traity medicine cabinet/mirror to remain.	s china commode wi shut-off valve, flap va Bid Cost: minate with vitreous ap, supply lines, full p	th a maximu alve and wax Base china sink or	m wat c seal. X	Quantity BATHRO er usage per Quantity BATHRO le-lite top wit	OM - I	HALF of 1.6 gallons. Total Cost HALF ormed sink. Include the on plates. Total Cost
Install a 17" height, 2 piece, close coupled, white, vitreous Include plastic or pressed wood white seat, supply pipe, so Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of lar single handled metal faucet with drain and pop-up, P- travanity medicine cabinet/mirror to remain. Bath Exhaust Fan Replace Install a ceiling or through-the-wall, exterior ducted, vent	s china commode wishut-off valve, flap va Bid Cost: minate with vitreous ap, supply lines, full p	Base th a maximu live and wax Base china sink or out ball type	m wat c seal. X r marb shut-c	Quantity BATHRO er usage per Quantity BATHRO le-lite top wit off valves & e	OM - I	Total Cost Total Cost HALF brined sink. Include the plates. Total Cost
17" Height Commode Replace Install a 17" height, 2 piece, close coupled, white, vitreous Include plastic or pressed wood white seat, supply pipe, s Vanity/ Counter Top/ Sink Install new vanity cabinet complete with counter top of lar single handled metal faucet with drain and pop-up, P- travanity medicine cabinet/mirror to remain. Bath Exhaust Fan Replace Install a ceiling or through-the-wall, exterior ducted, vent Repair any tear out.	s china commode wishut-off valve, flap va Bid Cost: minate with vitreous ap, supply lines, full p	Base th a maximu live and wax Base china sink or out ball type	m wat c seal. X r marb shut-c	Quantity BATHRO er usage per Quantity BATHRO le-lite top wit off valves & e	OM - I	Total Cost Total Cost HALF brined sink. Include the plates. Total Cost

GFCI Receptacle 20 AMP-HALF BATH

BATHROOM - HALF

Install a flush mounted, ground fault circuit interrupted, duplex receptacle and cover plate. Fish wire and repair all tear out as needed.

	Bid Cost:	Y	(=	•
	DIG C081	Base	Quantity	Total Cost
Prep & Paint Room Semi Gloss - HALF	and the state of the second	Market de la servición de la companya del companya del companya de la companya de	BATHROO	M - HALF
Remove or cover hardware and accessories not to be painted fungus, dirt, and dust from surfaces. Fill holes and cracks. Priwith owner's choice of low VOC acrylic SEMI-GLOSS latex. Fhardware, fixtures and accessories. Any moving of furniture reactions, walls and Trim	me all new mate Painting shall inc	rials and spot lude walls and	prime existing with	i acrylic latex. Top coa
	Bid Cost:		<=	1
,		Base	Quantity	Total Cost
Prep & Paint Room Flat-DEN	e de la composition	persons in a section of	DEN/OFFIC	CE/STUDY Exterio
fungus, dirt, and dust from surfaces. Fill holes and cracks. Pri with owner's choice of low VOC acrylic FLAT latex. Painting s Replace or uncover hardware, fixtures and accessories. Any * Ceilings ,Walls and Trim	shall include wall moving of furnitu	s and any ass ire required sh	ociated trim with S	EMI-GLOSS latex.
	Bid Cost:	Base	Quantity	Total Cost
Light Fixture Replace Replace or install a ceiling mounted 2 bulb or wall mounted 4	bulb strip, UL a			CE/STUDY Exterion hade and lamps.
	Dia 00011	Base	Quantity	Total Cost
Cabinets Base			Kitchen	• • • •
Replace base cabinets. Cabinets to be constructed of solid magnidelines & specifications for full requirements.	naple and plywo	od. No particle	board allowed. Se	ee contractor's manual
	Bid Cost: _		X	Total Cost
	Bid Cost: _	Base	Quantity	= Total Cost
Cabinets Wall		Base	Quantity Kitchen	
		Base	Quantity Kitchen	
Cabinets Wall Replace wall cabinets. Cabinets are to be constructed of so		Base ywood. No pai	Quantity Kitchen	

Prep & Paint Room Semi Gloss-KITCHEN

Remove or cover hardware and accessories not to be painted. Scrape loose, peeling, cracked and blistered areas. Clean oil, grease, fungus, dirt, and dust from surfaces. Fill holes and cracks. Prime all new materials and spot prime existing with acrylic latex. Top coat with owner's choice of low VOC acrylic SEMI-GLOSS latex. Painting shall include walls and any associated trim. Replace or uncover hardware, fixtures and accessories. Any moving of furniture required shall be included.

* Includes Ceiling, walls and Trim. Quantity Front Exterior **REPAIR -Handrails- FRONT PORCH** Install Code approved handrails on front porch. **Total Cost** Quantity Exterior **Light Fixture Exterior** Replace or install a UL approved, LED light fixture. Quantity **Total Cost BATHROOM-MAIN** Install 1 1/2" diameter S/S Grab Bars on 3 walls at height of 36" (include wood blocking in wall. Each bar must hold 300 pounds). Owners choice of locations. Base Quantity **Total Cost** All Contractor's Project Requirements The contractor is responsible for project requirements, including but limited to: Obtaining all permits required. Said permits shall include all items in this scope of work. Provide temporary toilet facilities from job start until the completion of work. Provide AS MANY roll-off dumpsters as needed without damaging the site. Collect construction debris using dust control methods. Remove dumpster and repair any evidence of the dumpsters use. Contractor may haul debris away daily using dump trailers. Quantity

Steel Bathtub - Remove and Replace

BATHROOM -MAIN

Install a 5' white, enameled, formed steel bathtub complete with slip-resistant surface, lever operated pop-up drain and overflow, PVC waste, single lever tub/shower diverter with water-saving shower head.

	Bid Cost:	x	X =	
		Base	Quantity	Total Cost
Ceramic Wall Tile -BATH MAIN	e gradi i di	BATHROOM- MAIN		
Install owner's choice ceramic wall tile over cement fiberboard trimmer pieces to complete installation. After at least 24 hours of grout and apply mildew resistant white silicone caulk at all sear	drying time, ap	ply latex based	portland cement gr	cap, stop, return and rout. Clean all excess
	Bid Cost:	x		
		Base	Quantity	Total Cost
Secure Wrought Iron Railing			REAR RAIL	s- WROUGHT IRON
Remove existing railing, repair anchor points as necessary and Code.	l reinstall secui	ely to meet the	railing requirement	ts of the Building
	Bid Cost:	х	<u> </u>	
		Base	Quantity	Total Cost
Refrigerator18 CF Frost Free			KITCHEN	
Dispose of old refrigerator. Install a 2 door, Energy Star rated fi match existing refrigerator like for like (i.e. volume, style (top as refrigerator with ice maker as well).	rost free refrige nd bottom or si	erator with at leaded by side, or it	ast 18 cubic feet. N f have existing ice n	lew refrigerator is to naker, install new
	Bid Cost: _		(=	
		Base	Quantity	Total Cost
Certification				
Contractor Name:	- MARKOONOH	Total Cost:		
Signature:			Date:	